




ШКИВЫ ЗУБЧАТЫЕ - ISO 5294 ДЛЯ КОНИЧЕСКИХ ВТУЛОК ТАПЕРБУШ


Н 300

Шаг 1/2" (12,7mm)


Для ремней шириной 3" (76,2mm)



18 F



19 F



20

Материал: Сталь (St)
Материал: Чугун (GG)

Описание	Артикул	Тип	Материал	Число зубьев	Втулка	Макс отверстие	dp	de	Df	Dm	Di	F	L	R	н° фланец	Вес, kg
TL 20 Н 300	22300020EMT	18F	St	20	1615	42	80,85	79,48	87		64,5	84,0	38,0	23,0	315	1,22
TL 21 Н 300	22300021EMT	18F	St	21	1615	42	84,89	83,52	91		65	84,0	38,0	23,0	316	1,52
TL 22 Н 300	22300022EMT	18F	St	22	1615	42	88,94	87,56	93		67	84,0	38,0	23,0	317	1,80
TL 23 Н 300	22300023EMT	18F	St	23	1615	42	92,98	91,61	97		70	84,0	38,0	23,0	318	2,04
TL 24 Н 300	22300024EMT	18F	St	24	1615	42	97,02	95,65	103		73,5	84,0	38,0	23,0	320	2,29
TL 25 Н 300	22300025EMT	18F	St	25	1615	42	101,06	99,69	106		77	84,0	38,0	23,0	321	2,54
TL 26 Н 300	22300026EMT	18F	St	26	1615	42	105,11	103,73	111		82	84,0	38,0	23,0	322	2,73
TL 27 Н 300	22300027EMT	18F	St	27	2012	50	109,15	107,78	115		85	84,0	32,0	26,0	323	2,54
TL 28 Н 300	22300028EMT	18F	St	28	2012	50	113,19	111,82	119		90,5	84,0	32,0	26,0	325	2,68
TL 30 Н 300	22300030EMT	18F	St	30	2012	50	121,28	119,90	127		98	84,0	32,0	26,0	327	3,21
TL 32 Н 300	22300032EMT	18F	St	32	2517	60	129,36	127,99	135		106	84,0	45,0	19,5	328	3,58
TL 36 Н 300	22300036EMT	18F	St	36	2517	60	145,53	144,16	152		121	84,0	45,0	19,5	334	4,99
TL 40 Н 300	22300040EMT	18F	St	40	2517	60	161,70	160,33	168		138	84,0	45,0	19,5	338	6,50
TL 44 Н 300	22300044EMT	19F	St	44	2517	60	177,87	176,50	184	119	152	86,0	45,0	20,5	339	7,55
TL 48 Н 300	22300048EMT	19F	St	48	2517	60	194,04	192,67	200	119	169	86,0	45,0	20,5	342	8,66
TL 60 Н 300	22300060EMT	20	GG	60	2517	60	242,55	241,18		119	223	86,0	45,0	20,5		7,42
TL 72 Н 300	22300072EMT	20	GG	72	2517	60	291,06	289,69		119	270	86,0	45,0	20,5		9,33
TL 84 Н 300	22300084EMT	20	GG	84	2517	60	339,57	338,20		119	320	86,0	45,0	20,5		11,19
TL 96 Н 300	22300096EMT	20	GG	96	3030	75	388,08	386,71		150	362	86,0	76,0	5,0		17,96
TL 120 Н 300	22300120EMT	20	GG	120	3030	75	485,10	483,73		150	460	86,0	76,0	5,0		22,23